

## LOGLIFT 140S




## LOGLIFT 140S BASIC DATA

Technical data	F140S 79	F140S 96
Max. lifting capacity (kNm)	136	129
Hydraulic outreach* (m)	7.9	9.6
Number of extensions	1	2
Outreach - lifting capacity, standard (m - kg)	3.0 - 4200 4.0 - 3250 5.0 - 2650 6.0 - 2260 7.0 - 1940 7.9 - 1640	3.0 - 3650 4.0 - 3100 5.0 - 2550 6.0 - 2160 7.0 - 1840 8.0 - 1580 9.0 - 1400 9.6 - 1250
Slewing system	Double	
Slewing angle (°)	425	
Slewing torque, gross (kNm)	32.1	
Max. working pressure (MPa)	26	
Recommended oil flow – fixed pump (I/min), 1-pump	80	
Recommended oil flow – fixed pump (I/min), 2-pump	2x80	
Min. recommended oil flow - variable displacement pump (I/min)	160	
Weight - High seat crane with standard stabilizer (kg)*	2180	2320
Weight - Cabin crane with standard stabilizer (kg)*	2590	2730

\* Weight with fixed pump system, oil weight included

Side view



min	1-1 max	1-2	1-3	1-4	1-5	1-6
305	7895	2450	1590	2365	2761	Ø 40, B=184
145	9595	2590	3150	2398	2761	Ø 40, B=184



## **BUILT TO PERFORM**

Hiab is the world's leading provider of on-road load handling equipment. Customer satisfaction is the first priority for us. Hiab's product range includes HIAB loader cranes, JONSERED recycling and forestry cranes, LOGLIFT forestry cranes, MOFFETT truck mounted forklifts and MULTILIFT demountables, as well as DEL, WALTCO and ZEPRO tail lifts.

hiab.com

Hiab is part of Cargotec. cargotec.com

**Disclaimer**. We reserve the right to make changes. Illustrations, drawings and data are not always in accordance with the latest version or standard model in production. The models in the pictures may present special equipment or colours.

BD-F140S-EN-WW\_190131